AMENDMENTS TO THE CLAIMS

50

1. (Previously Amended) The electric power steering apparatus of claim 7, wherein

the biasing member biases said worm shaft deflectable toward said worm wheel, in a deflective direction of said worm shaft.

2. (Original) The electric power steering apparatus of claim 1, wherein

said worm shaft is deflectable in a side of said worm shaft, interlocked with an output shaft of said electric motor and an interlocking member interlocking said worm shaft and said output shaft is provided therebetween.

3. (Original) The electric power steering apparatus of claim 1, wherein

said worm shaft is supported in a gear housing having a tapped hole, and said biasing member includes a screw body tightly fastened in said tapped hole and a spring body interposed between said screw body and said worm shaft.

4. (Original) The electric power steering apparatus of claim 1, wherein

Appl. No. 09/655,847

E John State of the State of th

said worm shaft is supported in a gear housing having a tapped hole, and said biasing member includes a screw body which is tightly fastened in said tapped hole and which is in contact with said worm shaft or a bearing fitted to said worm shaft.

DIX

- 5. (Withdrawn).
- 6. (Withdrawn).
- 7. (Currently Amended) An electric power steering apparatus, comprising:

an electric motor for steering assistance;

- a worm shaft on which a worm is disposed;
- a steering shaft on which a worm wheel is disposed and to which a rotary motion of said electric motor is transmitted through said worm shaft;
- a biasing member biasing, via a bearing, said worm shaft toward said worm wheel; and
 - a concave member accepting saidthe bearing; and
 - a housing for housing said bearing and said concave member.
 - 8. (Cancelled).

()

9. (New) An electric power steering apparatus, comprising:

an electric motor for steering assistance;

a worm shaft on which a worm is disposed;

a steering shaft on which a worm wheel is disposed and to which a rotary motion of said electric motor is transmitted through said worm shaft;

a biasing member biasing, via a bearing, said worm shaft toward said worm wheel, wherein a housing that directly holds the bearing is the same housing that holds the biasing member; and

a concave member accepting the bearing.